

WiNG

1.4 WNAME, WiNG. Extreme Networks, Zebra, Motorola Symbol. WiNG 5.8.3 5.8.3+.

(Externally Hosted Pages). : DNS Whitelist (WNAME), webpage external (), RADIUS (WNAME).

WNAME 172.16.130.13 - 80.

: http://documentation.extremenetworks.com/ExtremeWireless/WiNG_5.8_CRG_MN002230A01_EN.pdf.

:

```
!  
aaa-policy wname_policy  
  authentication server 1 host 172.16.130.13 secret 0 wname_radius  
  authentication server 1 nac  
  accounting server 1 host 172.16.130.13 secret 0 wname_radius  
!  
dns-whitelist wname_whitelist  
  permit 8.8.8.8  
  permit 172.16.130.13  
!  
captive-portal wname_portal  
  server host 172.16.130.11 !  
  
  server mode centralized !      - self, centralized, centralized-controller  
  
  inactivity-timeout 300  
  webpage-location external  
  webpage external login http://172.16.130.13/cp/wing?  
  webpage external welcome http://172.16.130.13/cp/wing\_welcome  
  webpage external fail http://172.16.130.13/cp/wing\_welcome  
  webpage external agreement http://172.16.130.13/cp/wing\_welcome  
  webpage external acknowledgement http://172.16.130.13/cp/wing\_welcome  
  webpage external registration http://172.16.130.13/cp/wing\_welcome  
  webpage external no-service http://172.16.130.13/cp/wing\_welcome  
  accounting radius  
  use aaa-policy wname_policy  
  use dns-whitelist wname_whitelist  
!  
wlan FreeWiFi  
  ssid FreeWiFi  
  bridging-mode local  
  authentication-type none  
  no client-client-communication  
  use captive-portal wname_portal  
  captive-portal-enforcement  
  accounting wait-client-ip  
  
  radius dynamic-authorization  
!
```

WNAME "" "", - "Motorola/Zebra WiNG", IP-, FreeRADIUS /etc/freeradius/clients.conf RADIUS-.

Изменение сервера доступа

Параметры

RADIUS

SNMP/TACACS+

Категории

Тип

Motorola/Zebra WiNG

Имя устройства

MZW

IP адрес (NAS-IP-Address)

172.16.130.13

Внешний IP адрес

192.168.1.1

Местоположение

Местоположение

Комментарий

Логин ?

Пароль ?

☒ Использовать счетчики аккаунтинга

☐ Менять местами счетчики приёма/передачи

☐ Определять имена устройств абонентов

☐ Принимать детализацию потоков NetFlow

получено 0 записей

получено 0 записей

Вкл.

Сохранить изменения

Закреть

WNAM RADIUS CoA "RADIUS secret key" CoA (: 3799), "RADIUS Dynamic Authorization" SSID - Advanced.