

FortiWLC

1.5 WNAM FortiWLC . FortiWLC (WNAM) HTTP/HTTPS- RADIUS- (WNAM). (FortiWLC 50D-VM 8.4.2, VMware).

RADIUS- . "RADIUS" "ADD" . RADIUS- , .

	RADIUS Profile Name	RADIUS IP	RADIUS Port	Remote RADIUS Server	RADIUS Relay AP-ID	MAC Address Delimiter	Password Type	Called-Station-ID Type	Owner	RADIUS Server Timeout	RADIUS Server Retries
	wnam_radius	77.241.1.1	1812	Off	1	Colon (:)	Shared Key	MacAddress:SSID	controller	2	3
	wnam_radius_acct	77.241.1.1	1813	Off	1	Colon (:)	Shared Key	MacAddress:SSID	controller	2	3

RADIUS- (WNAM - 77.241..).

Profile Name	wnam_radius
Description	WNAM Radius server
RADIUS IP	77.241.1.1
RADIUS Secret	*****
RADIUS Port	1812
Remote RADIUS Server	Off
RADIUS Relay AP-ID	1
MAC Address Delimiter	Colon (:)
Password Type	Shared Key
Called-Station-ID Type	MacAddress:SSID
COA	On
RADIUS Server Timeout	2
RADIUS Server Retries	3

RADIUS- (WNAM - 77.241..).

RADIUS Profiles - Update

Profile Name	wnam_radius_acct
Description	WNAM Radius Acct server Enter 0-128 chars.
RADIUS IP	77.241
RADIUS Secret	***** Enter 1- 64 chars.
RADIUS Port	1813 Valid range: [1024-65535]
Remote RADIUS Server	Off
RADIUS Relay AP-ID	1
MAC Address Delimiter	Colon (:)
Password Type	Shared Key
Called-Station-ID Type	MacAddress:SSID
COA	Off
RADIUS Server Timeout	2 Valid range: [1-20]
RADIUS Server Retries	3 Valid range: [1-10]

Captive- "Captive Portal" "Global Settings", "https" "Default" "Certificate".

Captive Portal - Global Settings

Global Settings	Captive Portal Profiles	Captive Portal Exemptions							
Internal Portal Settings <table border="1"> <tr> <td>Portal URL</td> </tr> <tr> <td>Protocol</td> <td><input checked="" type="radio"/> https <input type="radio"/> http</td> </tr> <tr> <td>Certificate</td> <td>--Default--</td> </tr> <tr> <td colspan="2">* Please make sure DNS server has the above redirection URL entry mapped to the Controller's IP address</td> </tr> </table>			Portal URL	Protocol	<input checked="" type="radio"/> https <input type="radio"/> http	Certificate	--Default--	* Please make sure DNS server has the above redirection URL entry mapped to the Controller's IP address	
Portal URL									
Protocol	<input checked="" type="radio"/> https <input type="radio"/> http								
Certificate	--Default--								
* Please make sure DNS server has the above redirection URL entry mapped to the Controller's IP address									

Captive- (WNAM-CP) "Captive Portal" "Captive Portal Profiles" .

Captive Portal Profiles

REFRESH	ADD	DELETE							
CP Name	Owner	CNA bypass	Authentication Type	Primary Profile	Secondary Profile	Primary Accounting	Secondary Accounting	Captive Portal External Server Type	Captive Portal Exemption
WNAM-CP	controller	Off	radius	wnam_radius		wnam_radius_acct		Fortinet-Connect	1

- Captive- - Captive- "Captive Portal" "Captive Portal Exemptions" .

Fortinet FortiWLC 8.4-2build-1 | FortiWLC-50D-VM 17:48:27 FWC-VM-50@192.168.97.3 admin

Captive Portal Exemptions

	Profile Name	Description	FQDN	Owner
1	wnam_pass		http://77.241.100.100/cp/fortiwlc	controller

Captive- (WNAM-CP), RADIUS- URL : http://77.241..cp/fortiwlc ("FQDN").

"Fortinet-Connect", NAT .

Edit Captive Portal Profile

CP Name: WNAM-CP

User Authentication

Authentication Type: radius

Radius Authentication

Primary Authentication: wnam_radius

Secondary Authentication: No Radius

Radius Accounting

Primary Accounting: wnam_radius_acct

Secondary Accounting: No Radius

Accounting Interim Interval: 60 [Valid range: [60-36000]]

External Portal Settings

External Server: Fortinet-Connect

External Portal URL: http://77.241.100.100/cp/fortiwlc

Public IP of Controller: 195.151.1.1

Advanced Settings

Session Timeout: 0 [Valid range: [0-1440]]

Activity Timeout: 0 [Valid range: [0-60]]

Session Caching Time: 1 [Valid range: [1-1440]]

CNA bypass: Off

WNAM (. . . "Edit Captive Portal Exemption" "Added FQDN" . . .)

Edit Captive Portal Exemptions

Profile Name	1
Description	<input type="text" value="wnam_pass"/> Enter 0-128 chars.
FQDN	<input type="text"/> Enter 1-256 chars.
+ ADD	
Added FQDN	
<input type="checkbox"/>	FQDN
<input type="checkbox"/>	http://77.241.150.1/
DELETE	
SAVE CANCEL	

, SSID (: sp_FWC-test) Captive- .

Security Profiles (3 entries) <small>?</small>													
	Security Profile Name	L2 Modes Allowed	Data Encrypt	Captive Portal	Captive Portal profile	MAC Filtering	Firewall Capability	Captive Portal Bypass For MAC Authentication	Firewall Filter ID	Passthrough Firewall Filter ID	802.11W - Management Frame Protection	Online Sign Up	Owner
<input type="checkbox"/>	default	Open	None	Disabled		Off	none	Off			disable	not-configured	controller
<input type="checkbox"/>	sp_FWC-test	Open	None	WebAuth	WNAM-CP	On	none	On		wnam_filter	disable	not-configured	controller

(wnam_filter), - SSID.

Security Profiles - Update

Profile Name	sp_FWC-test
SECURITY SETTINGS	
Online Sign Up	not-configured
Security Mode *	Open
CAPTIVE PORTAL SETTINGS	
Captive Portal	WebAuth
Captive Portal profile	WNAM-CP
Captive Portal Authentication Method	external
Passthrough Firewall Filter ID	wnam_filter
Enter 0-16 chars.	
MAC FILTERING SETTINGS	
MAC Filtering	On
ACL Environment State	Disabled
MAC Auth Primary RADIUS Profile Name	wnam_radius
MAC Auth Secondary RADIUS Profile Name	No RADIUS
MAC Accounting Primary RADIUS Profile Name	wnam_radius_acct
MAC Accounting Secondary RADIUS Profile Name	No RADIUS
FIREWALL SETTINGS	
Firewall Capability	none
GENERAL SETTINGS	
Captive Portal Bypass For MAC Authentication	On
Security Logging	On
Show Detail Info...	

("QoS" "QoS and Firewall Rules") , 80 WNAM.

Fortinet FortiWLC 8.4-2build-1 | FortiWLC-50D-VM 17:50:04 FWC-VM-50@192.168.97.3 admin

Monitor	QoS and Firewall Rules (9 entries)																																																																																																																																			
Configuration	Global Quality-of-Service Parameters QoS and Firewall Rules QoS Codec Rules Marking Management Packets																																																																																																																																			
System Config																																																																																																																																				
Security																																																																																																																																				
Wireless																																																																																																																																				
Wired																																																																																																																																				
Policies																																																																																																																																				
QoS																																																																																																																																				
Service Control																																																																																																																																				
Devices																																																																																																																																				
Access Control																																																																																																																																				
WIPS																																																																																																																																				
<table border="1"> <thead> <tr> <th>ID</th> <th>Destination IP</th> <th>Destination Netmask</th> <th>Destination Port</th> <th>Source IP</th> <th>Source Netmask</th> <th>Source Port</th> <th>Network Protocol</th> <th>Firewall Filter ID</th> <th>Packet minimum length</th> <th>Packet maximum length</th> <th>QoS Protocol</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0.0.0.0</td> <td>0.0.0.0</td> <td>1720</td> <td>0.0.0.0</td> <td>0.0.0.0</td> <td>0</td> <td>6</td> <td></td> <td>0</td> <td>0</td> <td>H.323</td> </tr> <tr> <td>2</td> <td>0.0.0.0</td> <td>0.0.0.0</td> <td>0</td> <td>0.0.0.0</td> <td>0.0.0.0</td> <td>1720</td> <td>6</td> <td></td> <td>0</td> <td>0</td> <td>H.323</td> </tr> <tr> <td>3</td> <td>0.0.0.0</td> <td>0.0.0.0</td> <td>5060</td> <td>0.0.0.0</td> <td>0.0.0.0</td> <td>0</td> <td>17</td> <td></td> <td>0</td> <td>0</td> <td>SIP</td> </tr> <tr> <td>5</td> <td>0.0.0.0</td> <td>0.0.0.0</td> <td>5060</td> <td>0.0.0.0</td> <td>0.0.0.0</td> <td>0</td> <td>6</td> <td></td> <td>0</td> <td>0</td> <td>SIP</td> </tr> <tr> <td>7</td> <td>0.0.0.0</td> <td>0.0.0.0</td> <td>5200</td> <td>0.0.0.0</td> <td>0.0.0.0</td> <td>0</td> <td>17</td> <td></td> <td>0</td> <td>0</td> <td>other</td> </tr> <tr> <td>8</td> <td>0.0.0.0</td> <td>0.0.0.0</td> <td>0</td> <td>0.0.0.0</td> <td>0.0.0.0</td> <td>5200</td> <td>17</td> <td></td> <td>0</td> <td>0</td> <td>other</td> </tr> <tr> <td>100</td> <td>77.241.1.■■■■■</td> <td>255.255.255.255</td> <td>80</td> <td>0.0.0.0</td> <td>0.0.0.0</td> <td>0</td> <td>6</td> <td>wnam_filter</td> <td>0</td> <td>0</td> <td>other</td> </tr> <tr> <td>101</td> <td>0.0.0.0</td> <td>0.0.0.0</td> <td>0</td> <td>77.241.■■■■■</td> <td>255.255.255.255</td> <td>80</td> <td>6</td> <td>wnam_filter</td> <td>0</td> <td>0</td> <td>other</td> </tr> <tr> <td>1000</td> <td>0.0.0.0</td> <td>0.0.0.0</td> <td>0</td> <td>0.0.0.0</td> <td>0.0.0.0</td> <td>0</td> <td>0</td> <td>wnam_filter</td> <td>0</td> <td>0</td> <td>other</td> </tr> </tbody> </table>													ID	Destination IP	Destination Netmask	Destination Port	Source IP	Source Netmask	Source Port	Network Protocol	Firewall Filter ID	Packet minimum length	Packet maximum length	QoS Protocol	1	0.0.0.0	0.0.0.0	1720	0.0.0.0	0.0.0.0	0	6		0	0	H.323	2	0.0.0.0	0.0.0.0	0	0.0.0.0	0.0.0.0	1720	6		0	0	H.323	3	0.0.0.0	0.0.0.0	5060	0.0.0.0	0.0.0.0	0	17		0	0	SIP	5	0.0.0.0	0.0.0.0	5060	0.0.0.0	0.0.0.0	0	6		0	0	SIP	7	0.0.0.0	0.0.0.0	5200	0.0.0.0	0.0.0.0	0	17		0	0	other	8	0.0.0.0	0.0.0.0	0	0.0.0.0	0.0.0.0	5200	17		0	0	other	100	77.241.1.■■■■■	255.255.255.255	80	0.0.0.0	0.0.0.0	0	6	wnam_filter	0	0	other	101	0.0.0.0	0.0.0.0	0	77.241.■■■■■	255.255.255.255	80	6	wnam_filter	0	0	other	1000	0.0.0.0	0.0.0.0	0	0.0.0.0	0.0.0.0	0	0	wnam_filter	0	0	other
ID	Destination IP	Destination Netmask	Destination Port	Source IP	Source Netmask	Source Port	Network Protocol	Firewall Filter ID	Packet minimum length	Packet maximum length	QoS Protocol																																																																																																																									
1	0.0.0.0	0.0.0.0	1720	0.0.0.0	0.0.0.0	0	6		0	0	H.323																																																																																																																									
2	0.0.0.0	0.0.0.0	0	0.0.0.0	0.0.0.0	1720	6		0	0	H.323																																																																																																																									
3	0.0.0.0	0.0.0.0	5060	0.0.0.0	0.0.0.0	0	17		0	0	SIP																																																																																																																									
5	0.0.0.0	0.0.0.0	5060	0.0.0.0	0.0.0.0	0	6		0	0	SIP																																																																																																																									
7	0.0.0.0	0.0.0.0	5200	0.0.0.0	0.0.0.0	0	17		0	0	other																																																																																																																									
8	0.0.0.0	0.0.0.0	0	0.0.0.0	0.0.0.0	5200	17		0	0	other																																																																																																																									
100	77.241.1.■■■■■	255.255.255.255	80	0.0.0.0	0.0.0.0	0	6	wnam_filter	0	0	other																																																																																																																									
101	0.0.0.0	0.0.0.0	0	77.241.■■■■■	255.255.255.255	80	6	wnam_filter	0	0	other																																																																																																																									
1000	0.0.0.0	0.0.0.0	0	0.0.0.0	0.0.0.0	0	0	wnam_filter	0	0	other																																																																																																																									

"QoS"

FORTINET		FortiWLC 8.4-2build-1 FortiWLC-50D-VM	17:50:26	FWC-VM-50@192.168.97.3	
<ul style="list-style-type: none"> █ Monitor ██ Configuration > System Config > Security > Wireless > Wired ▀ Policies QoS Service Control > Devices > Access Control > WIPS ▀ Maintenance 	ID	100	Match	Flow Class	
	Destination IP	77.241.1.1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
	Destination Netmask	255.255.255.255	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
	Destination Port	80	Valid range: [0-65535]	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Source IP	0.0.0.0	<input type="checkbox"/>	<input type="checkbox"/>	
	Source Netmask	0.0.0.0	<input type="checkbox"/>	<input type="checkbox"/>	
	Source Port	0	Valid range: [0-65535]	<input type="checkbox"/>	<input type="checkbox"/>
	Network Protocol	6	Valid range: [0-255]	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Firewall Filter ID	wnam_filter	Enter 0-16 chars.	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	Packet minimum length	0	Valid range: [0-1500]	<input type="checkbox"/>	<input type="checkbox"/>
	Packet maximum length	0	Valid range: [0-1500]	<input type="checkbox"/>	<input type="checkbox"/>
	QoS Protocol	other	<input type="button" value="▼"/>		
	Average Packet Rate	0	Valid range: [0-200]		
	Action	FORWARD	<input type="button" value="▼"/>		
	Token Bucket Rate	0	<input checked="" type="checkbox"/> Kbps <input type="checkbox"/> Mbps Valid range: [0-1000]		
Priority	0	Valid range: [0-8]			
Traffic Control	Off	<input type="button" value="▼"/>			
DiffServ Codepoint	DiffServ Disabled	<input type="button" value="▼"/>			
Qos Rule Logging	Off	<input type="button" value="▼"/>			

WNAM

WNAM "" "",

Изменение сервера доступа

Параметры **RADIUS**

Тип	Имя устройства
FortiWLC	
IP адрес (NAS-IP-Address)	Внешний IP адрес
192.168.97.3	195.151.***.***
Местоположение	
Mercury tower	
Комментарий	
Вход	Пароль
admin	*****
<input checked="" type="checkbox"/> Использовать счетчики аккаунтинга	
<input type="checkbox"/> Менять местами счетчики приёма/передачи	
<input type="checkbox"/> Определять имена устройств абонентов	
<input type="checkbox"/> Принимать детализацию потоков NetFlow	

Вкл. **Сбросить сессии** **Удалить** **Сохранить изменения** **Закрыть**

```
radius-profile wnam_radius
description "WNAM Radius server"
ip-address 77.241.xxx.xxx
coa on
radius-timeout 2
radius-retries 3
radius-version 0
key wnam_radius
port 1812
remote-radius-server off
radius-relay-apid 1
mac-delimiter colon
password-type shared-secret
called-station-id-type macaddress-ssid
owner controller
exit
radius-profile wnam_radius_acct
description "WNAM Radius Acct server"
ip-address 77.241.xxx.xxx
coa off
radius-timeout 2
radius-retries 3
radius-version 0
key wnam_radius
port 1813
remote-radius-server off
radius-relay-apid 1
mac-delimiter colon
password-type shared-secret
called-station-id-type macaddress-ssid
owner controller
exit
```

```
security-profile sp_FWC-test
    security-version 0
    key-rotation disabled
    management-frame-protection-11w disable
    allowed-12-modes open
    online-sign-up not-configured
    captive-portal webauth
    captive-portal-profile WNAM-CP
    captive-portal-auth-method external
    psk key ""
    firewall-capability none
    passthrough-firewall-filter-id wnam_filter
    firewall-filter-id ""
    security-logging on
    owner controller
    static-wep key ""
    static-wep key-index 1
    captive-portal-bypass-mac
    macfiltering
    mac-filter-radius-server primary wnam_radius
    mac-filter-radius-server secondary ""
    mac-filter-acct-radius-server primary wnam_radius_acct
    mac-filter-acct-radius-server secondary ""
    mac-filter-state disabled
    rekey period 0
    group-rekey interval 0
    bksa-caching-period 0
    radius-server primary ""
    radius-server secondary ""
    auth-suplicant-timeout 30
    auth-server-timeout 30
    auth-max-request 4
    pae-max-reauth 4
    pae-txperiod 30
    eapol-key-retries
    no kddi
    no shared-authentication
    no rekey period
    no 8021x-network-initiation
    no pmk-caching
    no reauth
exit
```

```
qosrule 100 netprotocol 6 qosprotocol other
firewall-filter-id wnam_filter
firewall-filter-id-match on
dstip 77.241.xxx.xxx
dstip-match on
dstmask 255.255.255.255
dstport 80
dstport-match on
srcip 0.0.0.0
srcmask 0.0.0.0
srcport 0
netprotocol-match on
action forward
priority 0
avgpacketrate 0
tokenbucketrate 0
dscp disabled
qosrulelogging off
qosrule-logging-frequency 60
packet-min-length 0
packet-max-length 0
no trafficcontrol
owner controller
exit
qosrule 101 netprotocol 6 qosprotocol other
firewall-filter-id wnam_filter
dstip 0.0.0.0
dstmask 0.0.0.0
dstport 0
srcip 77.241.xxx.xxx
srcip-match on
srcmask 255.255.255.255
srcport 80
action forward
priority 0
avgpacketrate 0
tokenbucketrate 0
dscp disabled
qosrulelogging off
qosrule-logging-frequency 60
packet-min-length 0
packet-max-length 0
no trafficcontrol
owner controller
exit
qosrule 1000 netprotocol 0 qosprotocol other
firewall-filter-id wnam_filter
dstip 0.0.0.0
dstip-match on
dstmask 0.0.0.0
dstport 0
dstport-match on
srcip 0.0.0.0
srcip-match on
srcmask 0.0.0.0
srcport 0
srcport-match on
action drop
priority 0
avgpacketrate 0
tokenbucketrate 0
dscp disabled
qosrulelogging off
qosrule-logging-frequency 60
packet-min-length 0
packet-max-length 0
no trafficcontrol
owner controller
exit
```

```
essid FWC-test
enable
security-profile sp_FWC-test

captive-portal-exemption-profile 1
fqdn-names http://77.241.xxx.xxx/
description wnam_pass
exit

captive-portal-profile WNAM-CP
port 0
cna-bypass off
radius-profile primary wnam_radius
radius-profile secondary ""
captive-portal-external-url http://77.241.xxx.xxx/cp/fortiwlcc
captive-portal-external-ip 195.151.112.84
13user-session-timeout 1
session-timeout 0
activity-timeout 0
authentication-type radius
accounting-radius-profile primary wnam_radius_acct
accounting-radius-profile secondary ""
accounting-radius-profile interim-interval 60
external-server fortinet-connect
captive-portal-exemption-profile 1
owner controller
exit
captive-portal-global-settings captive-portal-certificate default
captive-portal-global-settings redirection-protocol https
```