

Aruba 6.4

1.2.607 WNAM Aruba (Hewlett Packard Enterprise). Aruba3200 ArubaOS 6.4.2.4.

:

- IP (): 89.11.95.20
- IP (): 172.16.0.1
- IP WNAM: 89.11.95.19
- VLAN : 162
- SSID: aruba

Aruba WNAM , , (SSID VLAN), , . Aruba.

, , Apply.

RADIUS- (WNAM), "Configuration - Security - Authentication" - **wnam_radius**, (- wnam_radius), , :

arubaMOBILITY CONTROLLER 1

DashboardMonitoringConfigurationDiagnosticsMaintenanceSave Configuration

WIZARDSAPControllerCampus WLANRemote APWIPAirWaveNETWORKControllerVLANsPortsCellular ProfileIPSECURITY> AuthenticationAccess ControlWIRELESSAP ConfigurationAP InstallationMANAGEMENTGeneralAdministrationCertificatesSNMPLoggingClockGuest ProvisioningCaptive PortalSMTPBandwidth CalculatorThresholdADVANCED SERVICESRedundancyAirGroupIP MobilityStateful Firewall

Security > Authentication > ServersServersAAA ProfilesL2 AuthenticationL3 AuthenticationUser RulesAdvanced

Server Groupdefaultinternalwnam_radius_sgRADIUS Serverwnam_radiusLDAP ServerInternal DBTacacs Accounting ServerTACACS ServerX3ML API ServerRPC 3576 ServerWindows Server

RADIUS Server > wnam_radius

Show ReferenceSave AsReset

Host	89.11.95.19
Key	*****Retype:*****
Auth Port	1812
Acct Port	1813
Retransmits	3
Timeout	5 sec
NAS ID	Aruba
NAS IP	89.11.95.20
Enable IPv6	
NAS IPv6	
Source Interface	vlanidip6addr
Use MDS	
Use IP address for calling station ID	
Mode	
Lowercase MAC addresses	
MAC address delimiter	colon
Service-type of FRAMED-USER	
called-station-id	csid_type macaddrinclude_ssid enablecsid_delimiter colon

NAS IP , , WNAM /etc/freeradius/clients.conf.

wnam_radius_sg :

arubaMOBILITY CONTROLLER 1

DashboardMonitoringConfigurationDiagnosticsMaintenanceSave Configuration

WIZARDSAPControllerCampus WLANRemote APWIPAirWaveNETWORKControllerVLANsPortsCellular ProfileIPSECURITY> AuthenticationAccess ControlWIRELESSAP ConfigurationAP InstallationMANAGEMENTGeneralAdministrationCertificatesSNMPLoggingClockGuest ProvisioningCaptive PortalSMTPBandwidth CalculatorThresholdADVANCED SERVICESRedundancyAirGroupIP MobilityStateful Firewall


Security > Authentication > ServersServersAAA ProfilesL2 AuthenticationL3 AuthenticationUser RulesAdvanced

Server Groupdefaultinternalwnam_radius_sgRADIUS Serverwnam_radiusLDAP Server


Server Group

Instance	Servers out of Service	Actions
default		Show ReferenceDelete
internal		Show ReferenceDelete
wnam_radius_sg		Show ReferenceDelete
		Add


RFC3567, :



"AAA Profiles" , wnam_aaa_profile.



"Initial role". " " . Interim Accounting:



- wnam_radius_sg :

aruba MOBIILITY CONTROLLER | [Log out remote](#)

Dashboard Monitoring **Configuration** Diagnostics Maintenance Save Configuration

WIZARDS
AP
Controller
Campus WLAN
Remote AP
WIP
AirWave
NETWORK
Controller
VLANs
Ports
Cellular Profile
IP
SECURITY
Authentication
Access Control
WIRELESS
AP Configuration
AP Installation
MANAGEMENT
General
Administration
Certificates
SNMP
Logging
Clock
Guest Provisioning
Captive Portal

Security > Authentication > Profiles

Servers AAA Profiles L2 Authentication L3 Authentication User Rules Advanced

AAA

RADIUS Accounting Server Group > **wnam_radius_sg** [Show Reference](#) [Save As](#) [Reset](#)

Fail Through ☐ N/A
Load Balance ☐ internal

Servers

Name	Server-Type	trim-FQDN	Match-Rule
wnam_radius	Radius	No	

[New](#) [Delete](#)

Server Rules

Priority	Attribute	Operation	Operand	Type	Action	Value	Validated
New							

[New](#) [Delete](#)

MAC Authentication
MAC Authentication Server Group wnam_radius_sg
802.1X Authentication
802.1X Authentication Server Group
RADIUS Accounting Server Group wnam_radius_sg
XML API server
RFC 3576 server

"L3 Authentication". **wnam_captive_portal**:

aruba MOBIILITY CONTROLLER | [Log out remote](#)

Dashboard Monitoring **Configuration** Diagnostics Maintenance Save Configuration

WIZARDS
AP
Controller
Campus WLAN
Remote AP
WIP
AirWave
NETWORK
Controller
VLANs
Ports
Cellular Profile
IP
SECURITY
Authentication
Access Control
WIRELESS
AP Configuration
AP Installation
MANAGEMENT
General
Administration

Security > Authentication > L3 Authentication

Servers AAA Profiles L2 Authentication L3 Authentication User Rules Advanced

Captive Portal Authentication

Captive Portal Authentication Profile

Instance	Actions
wnam_captive_portal	Show Reference Delete
wnam_captive_portal	Show Reference Delete
wnam_captive_portal	Show Reference Delete
wnam_captive_portal	Show Reference Delete

[Add](#)

WISPr Authentication
VPN Authentication
Stateful NTLM Authentication
Stateful Kerberos Authentication
VSA Authentication
VSA Connection
VSA Web Authentication

Login page , WNAM, : <http://89.11.95.19/cp/aruba>

Welcome page (). (White list) **wnam_destination**.

aruba MOBIILITY CONTROLLER | [Log out remote](#)

Dashboard Monitoring **Configuration** Diagnostics Maintenance Save Configuration

WIZARDS
AP
Controller
Campus WLAN
Remote AP
WIP
AirWave
NETWORK
Controller
VLANs
Ports
Cellular Profile
IP
SECURITY
Authentication
Access Control
WIRELESS
AP Configuration
AP Installation
MANAGEMENT
General
Administration
Certificates
SNMP
Logging
Clock
Guest Provisioning
Captive Portal
SMTP
Bandwidth Calculator
Threshold
ADVANCED SERVICES
Redundancy
AirGroup
IP Mobility
Stateful Firewall
Threshold
ADVANCED SERVICES
Redundancy
AirGroup
IP Mobility
Stateful Firewall
External Services
VPN Services
Wired Access
All Profiles
[E-mail Support](#)

Security > Authentication > L3 Authentication

Servers AAA Profiles L2 Authentication **L3 Authentication** User Rules Advanced

Captive Portal Authentication

- cp-preview
- cp_test_cp_prof
- default
- guestnet
- wnam_captive_portal**

Server Group: wnam_radius_gp

Captive Portal Authentication Profile > wnam_captive_portal [Show Reference](#) [Save As](#) [Reset](#)

Default Role	guest
Default Guest Role	guest
Redirect Pause	10 sec
User Login	<input checked="" type="checkbox"/>
Guest Login	<input checked="" type="checkbox"/>
Logout popup window	<input type="checkbox"/>
Use HTTP for authentication	<input checked="" type="checkbox"/>
Logon wait minimum wait	5 sec
Logon wait maximum wait	10 sec
Logon wait CPU utilization threshold	60 %
Max Authentication failures	0
Show FQDN	<input type="checkbox"/>
Authentication Protocol	PAP
Login page	http://89.11.95.19/cp/arub
Welcome page	http://89.11.95.19/cp/arub
Show Welcome Page	<input type="checkbox"/>
Add switch IP address in the redirection URL	<input checked="" type="checkbox"/>
Adding user vlan in redirection URL	<input checked="" type="checkbox"/>
Add a controller interface in the redirection URL	address 89.11.95.20
Allow only one active user session	<input type="checkbox"/>
White List	wnam_destination Delete ipv6-reserved-range Add
Black List	Delete ipv6-reserved-range Add
Show the acceptable use policy page	<input type="checkbox"/>
User idle timeout	seconds
Redirect URL	
Bypass Apple Captive Network Assistant	<input checked="" type="checkbox"/>
URL Hash Key	Retype:

Commands [Apply](#) [View Commands](#)

(Interim stats). IP , RADIUS- NAS-IP-Address. WNAM (172.16.0.1):

aruba MOBIILITY CONTROLLER | [Log out remote](#)

Dashboard Monitoring **Configuration** Diagnostics Maintenance Save Configuration

WIZARDS
AP
Controller
Campus WLAN
Remote AP
WIP
AirWave
NETWORK
Controller
VLANs
Ports
Cellular Profile
IP
SECURITY
Authentication
Access Control
WIRELESS
AP Configuration
AP Installation

Security > Authentication > Advanced

Servers AAA Profiles L2 Authentication L3 Authentication User Rules **Advanced**

Authentication Timers

User Idle Timeout	300 sec
Authentication Server Dead Time (min)	10
Logon User Lifetime (min)	5
User Interim stats frequency	600 sec

RADIUS Client


NAS IPv4 Address	172.16.0.1
Source Interface v4	<-- None
NAS IPv6 Address	::1
Source Interface v6	<-- None

DNS Query Interval

DNS Query Interval (min)	15
--------------------------	----

[Apply](#)

"Configuration - Security - Access control". **guest-logout**:



Aruba .

WNAM Aruba, IP-, NAS-IP-Address RADIUS- . - Aruba (DHCP-), NetFlow.

Изменение сервера

Тип

Aruba

IP адрес

172.16.0.1

Местоположение

Aruba LAB_A

Логин

Пароль

☒ Использовать счетчики аккаунтинга

☐ Определять имена абонентов

☐ Принимать детализацию потоков NetFlow

Сбросить сессии

Удалить

Сохранить изменения

Заккрыть

:

```
ip access-list standard wnam_whitelist
permit host 89.11.95.19
```

```
netdestination wnam_destination
 host 89.11.95.19

ip access-list session wnam_access
 user host 89.11.95.19 svc-http permit

user-role guest-logon
 captive-portal "wnam_captive_portal"
 access-list session ra-guard
 access-list session logon-control
 access-list session captiveportal
 access-list session v6-logon-control
 access-list session captiveportal6

user-role guest
 access-list session global-sacl
 access-list session apprf-guest-sacl
 access-list session ra-guard
 access-list session http-acl
 access-list session https-acl
 access-list session dhcp-acl
 access-list session icmp-acl
 access-list session dns-acl
 access-list session v6-http-acl
 access-list session v6-https-acl
 access-list session v6-dhcp-acl
 access-list session v6-icmp-acl
 access-list session v6-dns-acl
 access-list session wnam_access

aaa rfc-3576-server "89.11.95.19"
 key XXX

aaa authentication mac "wnam_mac_authprofile"
 delimiter colon
 case upper

aaa authentication-server radius "wnam_radius"
 host "89.11.95.19"
 key XXX
 nas-identifier "Aruba"
 nas-ip 89.11.95.20
 mac-delimiter colon
 called-station-id type macaddr include-ssid enable delimiter colon

aaa server-group "wnam_radius_sg"
 auth-server wnam_radius

aaa profile "wnam_aaa_profile"
 initial-role "guest-logon"
 mac-server-group "wnam_radius_sg"
 radius-accounting "wnam_radius_sg"
 radius-interim-accounting
 rfc-3576-server "89.11.95.19"

aaa authentication captive-portal "wnam_captive_portal"
 server-group "wnam_radius_sg"
 guest-logon
 no logout-popup-window
 protocol-http
 login-page "http://89.11.95.19/cp/aruba"
 welcome-page "http://89.11.95.19/cp/aruba?welcome"
 no enable-welcome-page
 switchip-in-redirection-url
 user-vlan-in-redirection-url
 ip-addr-in-redirection-url "89.11.95.20"
 white-list "wnam_destination"
 apple-cna-bypass
```



```
wlan virtual-ap "guestnet"  
  aaa-profile "wnam_aaa_profile"  
  ssid-profile "cittel-aruba"  
  vlan 162  
  band-steering  
  broadcast-filter all  
  deny-inter-user-traffic  
  dos-prevention  
  wmm-traffic-management-profile "wmm"  
!
```

```
ap-group "guestnet"  
  virtual-ap "guestnet"
```